



GE BUDDY DOWNLIGHT

DESCRIPTION

The GE Buddy downlight offers a clean line with framework sitting completely flush to the ceiling. This downlight is IP44 rated and would be great to use in bathroom, kitchen or outdoor areas. The frame is made from Aluminium and it has a thermal plastic heatsink. This downlight is dimmable using the following dimmers: LUMEX Load Smart LT1D450LS, DIGINET LED Smart MEDM, Clipsal 31E2PUDM / 31E22RUDM / 32E450TM / 32E450UDM / 32ELEDM, HPM: Cat. 400T, Lucci SKU 290998 / 290997. It is highly recommended to use Lucci SKU 290998 / 290997 dimmers with this light fitting.

SPECIFICATIONS

SKU	G12047L
Dimmable	Yes
Recommended Dimmers	Lucci LEDlux SKU# 290998, 290997, 299043, 290989, 290992, 290993, 290994. Buster + Punch SKU# 299098, 299099, 299100 299101. Artisan SKU#197015, 197016, 197017, 197018.
IP Rating	40
Socket type	Integrated LED
Globe Quantity	0
Wattage Max	8W
Globe Colour Temperature	Warm White
Kelvins	3000K
Lumens	700
CRI	80
Efficacy	87.5
Beam Angle	110 degrees
Field Angle	160 degrees
Average Rated Life	25,000 hours
Cut Out Size (mm)	90
IC (Insulation Contact) Rated	IC-4
Material	ABS
Voltage	240V
Double Insulated	Yes
Sdcm	=6
Operating Temperature	-20 degrees to 40 degrees
Ambient Temperature	25 degrees
Brand	GE
Globe Included	Yes
Product Type	Lighting
Cable Length	400mm
Colour/Finish	Black

[Click here for installation instruction](#)

