



GE CHAMP TRI-COLOUR DOWNLIGHT

DESCRIPTION

The GE Champ downlights offer a clean line and low glare profile with a more recessed silhouette. The downlights have a weatherproof IP44 rating, and are IC-4 rated. These downlights are dimmable with the following dimmers: Lucci LEDlux SKU#290998, SKU #290997; LUMEX Load Smart LT1D450LS; DIGINET LED Smart MEDM; Clipsal 31E2RUDM, 32E450TM, 32E450UDM, 31E2PUDM and 32ELEDM; HPM: Cat. 400T.

SPECIFICATIONS

SKU	G13224L
Dimmable	Yes
Recommended Dimmers	Lucci LEDlux SKU# 290998, 290997, 299043, 290989, 290992, 290993, 290994. Buster + Punch SKU# 299098, 299099, 299100 299101. Artisan SKU#197015, 197016, 197017, 197018.
IP Rating	40
Socket type	Integrated LED
Globe Quantity	1
Wattage Max	10W
Globe Colour Temperature	Warm White/Cool White/Day Light
Kelvins	3000K/4000K/5000K
Lumens	700
CRI	90
Efficacy	70
Beam Angle	110 degrees
Field Angle	160 degrees
Average Rated Life	25,000 hours
Cut Out Size (mm)	90
IC (Insulation Contact) Rated	IC-4
Material	Aluminium
Voltage	240V
Double Insulated	Yes
Sdcm	=6 (3000K/5000K) =7 (4000K)
Operating Temperature	-20 degrees to 40 degrees
Ambient Temperature	50 degrees
Brand	GE
Globe Included	Yes
Product Type	Lighting
Cable Length	300mm
Colour/Finish	Black

[Click here for installation instruction](#)